# 177401

## ZP755R-2R room sounder C/W cover

### General

The ZP755R-2R is a RED, addressable loop powered room sounder or us on ZP fire alarm systems. The ZP755R-2R combines a detector base and audible sounder in a single stylish moulding.

The ZP755R-2R is developed for applications in individual rooms, sleeping accommodation or small compartments where it is impractical or unnecessary for the sounder and detector to be combined. Installed directly onto a ZP7 wiring loop - the ZP755R-2R enables the system designer to offer a complete addressable system on a single pair of wires. Installation costs are greatly reduced, whilst system integrity, sounder options and programmed alarm organisation are significantly increased. Time on site is further reduced as the moulding plugs directly into a first fix base – eliminating the need for any wiring directly to the device.

### Advanced acoustic design

High efficiency acoustic design and a low energy, sound gun transducer, enable combinations of up to 60 sensors and 60 sounders to be connected to a 1 km loop of 1.5 mm² cable. In systems where loop lengths or current requirements are excessive, the ZP755R-2R sounders can be locally powered from an external power supply.

### Output Test and Tone Selection

The ZP755 range of notification devices features a unique self-test facility which is automatically activated during routine sounder testing. A built in microphone circuit measures sound output level and automatically signals the sounder address and location to the control panel, should the output test fail.

Continuous, intermittent and two-tone outputs are available from which any combination can be chosen to provide alert and evacuate for two stage alarms. Sound types comply with most international codes (e.g. BS 5839 Part 1 recommended frequencies). The ZP755R-2R features a sound output of up to 90dBA and a volume control for areas where a reduced sound output is required.



### Details

- Powered directly from the ZP loop
- Up to 60 detectors and 60 sounders directly on the loop wiring
- Plug in base – no direct wiring connections
- High efficiency sound gun transducer
- Wide range of international sound types and frequencies
- EN54:3 Approved and CPR certified

# 177401
## ZP755R-2R room sounder C/W cover

## Technical specifications

### General

| | |
|---|---|
| Compatibility | All ZP7 addressable systems |
| Addressing method | DIP Switches |
| Monitoring | Device removal, Device type, Open circuit, Short circuit, Sound output |
| Addressing method | 7 way dipswitch |

### Electrical

| | |
|---|---|
| Operating voltage | Loop powered: 19.5 to 20.5 V<br>Externally powered:18 to 30 VDC |

### Sounder

| | |
|---|---|
| Output level | <70 dB(A) (tone dependant) |
| Selectable tones | Sound types: User configurable |

### Physical

| | |
|---|---|
| Physical dimensions | 127 x 69 mm (Ø x H) |
| Net weight | 205 g |
| Colour | Red |
| Mounting type | Surface mount |
| Material | Moulded thermoplastic |
| Mounting | Surface mount with plug in base - SPB-2R (White) |

### Environmental

| | |
|---|---|
| Operating temperature | -10 to +60°C |
| Storage temperature | -20 to +70°C |
| Relative humidity | 10 to 95% noncondencing |
| Environment | Indoor |
| IP rating | IP21C |

### Regulatory

| | |
|---|---|
| Certification | CPR, EN54-3 |

### Loop current

| | |
|---|---|
| Quiescent (when loop powered) | 820 µA |
| Active (when loop powered) | 4.5 mA |
| Quiescent (when externally powered) | 470 µA |
| Active (when externally powered) | 500 µA |

### Devices per loop (max.)

| | |
|---|---|
| | 60 (1 km loop of 1.5 mm² cable, 50 m to first device) |

### Wiring

| | |
|---|---|
| | 2 core loop |

### Compatible products

| Category | Reference | Description |
|---|---|---|
| Notification device | 70802 | Red Cap for ZP755B Series Notification Devices |
| Notification device | SPB-2R | Plug-in Base, RED |



KIDDE COMMERCIAL

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 16 October 2026 - 11:30