DM700KY-N

Manual Call Point Yellow, 2-Position Keyswitch, Surface Mount

General

The DM700KY-N is a high quality, yellow plastic manual call point with key switch.

The key switch has 2 positions, with the key being trapped in one position and removable in the other. Changing between these positions require the turn of the key through a 90° angle. It offers three electrical connections, which already come fitted with flying leeds. One of these connections are common, while the tuning of the key result in the change over between the other two.

Construction

The robust switching device comprises a main housing and a front plate. It is fitted to the plate which simply snaps into the main housing and is permanently located in place with fixing screws. All units are supplied with 2 sturdy keys.



Details

- Easy to install
- High quality key switch
- Operates after long period of disuse
- Preformed mounting slots
- Surface mount

DM700KY-N

Manual Call Point Yellow, 2-Position Keyswitch, Surface Mount

Technical specifications

Electrical

Operating voltage	250 VAC (max.)
Current consumption	2 A @ 250 VAC (max.) 4 A @ 125 VAC (max.) 4 A @ 28 VDC (max.)

Physical

Physical dimensions	87 x 87 x 52 mm (W x H x D)
Net weight	166 g
Colour	Gul
Mounting type	Ytmontering

Environmental

Operating temperature	-20 to +55°C
Relative humidity	0 to 90% noncondensing
Environment	Indendør
IP rating	IP21

Electrical (switch specifications)

Maximum voltage	250 VAC

Mechanical

Functional marking	"EXTINGUISHANT ABORT"

Compatible products

Category	Reference	Description
Detection device	DMN782	Hinged transparent MCP protection cover
Detection device	DMN787Y	Surface Mounting Box With Earth Connector, Yellow

EDWARDS
Built for Resilience

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 23 September 2025 - 16:20