DI-9101E

GST Intelligent DI-9000E Series Addressable Multisensor (Optical/Heat)

General

The Intelligent DI-9101E multisensor combines both smoke and heat sensors to facilitate fast and reliable operation. It allows for 2 different smoke sensitivity levels together with the flexibility of either fixed temperature or rate-of-rise heat detection support.

Overview

The GST DI-91xxE series intelligent detectors all feature the latest GST digital loop protocol and are compatible with the GST200N and GST-IFP4E intelligent fire alarm control panels. This enhanced digital communication protocol offers the possibility for the detectors to raise an alarm within 1 second, allowing more control and better and faster processing at the CIE.

All the DI-9000E series detectors may be installed onto the common detector base and allow for the connection of a common remote indicator.



Details

- Electronic addressing safeguarding against uncontrolled address changes
- Drift compensation allows for good environmental adaptability
- Self-diagnostic testing ensuring reliability at all times
- Local reed-switch test activation for easy maintenance
- Chamber contamination checking
- Alarm LED with 360° visibility
- Remote indicator output
- Configurable polling LED support
- 2 Smoke sensitivity levels
- LPCB marked

DI-9101E

GST Intelligent DI-9000E Series Addressable Multisensor (Optical/Heat)

Technical specifications

General

Status indication	LED
Compatibility	GST DI-9000E systems
Alarm levels	2
Connectivity	2-wire loop & remote indicator
Addressing method	Electronic

Electrical

Power supply type	Loop powered
Operating voltage	24 VDC
Current consumption	800 µA (quiescent) 1.8 mA (alarm)

Detection

Detection principle	Optical light scatter and/or heat
Rate-of-rise	Class A2R

Output

Output quantity	1

Physical

Physical dimensions	100 x 54.5 mm (Ø x H)
Colour	White
Mounting type	Ceiling mount
Material (body)	Plastic

Environmental

Vandal proof	No
Operating temperature	-10 to +50°C
Relative humidity	< 95% noncondensing
Environment	Indoor

Regulatory

Compliancy	CE, REACH, RoHS, WEEE
Certification	CPR
Standards	EN54-5, EN54-7

Compatible products

Category	Reference	Description
Detection device	DB-01	DC9000 / DI9000 Series standard point detector base
Detection device	DC-9504E	DI-9000E Series Innovation Detector base w/ Isolator
Notification device	C-9314P	DC9000 / DI9000 Series conventional remote indicator

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 12 June 2024 - 6:13