GST200N-2

GST200N Addressable 2 Loop Panel (English)

Product overview

GST200N Intelligent Fire Alarm Control Panels are designed in comply with EN54-2 and EN54-4 standard with qualities of simple installation, operation, and easy maintenance. 1-2 loop addressable panel is suitable for small buildings like office, restaurant, store, shop, etc.



Details

- Max. 30 zones, each zone has its own alarm and fault/disable indicator and a label
- 2-loop panel capacity 477 addressable devices
- Compatible with GST intelligent and digital products
- 8 lines x 18 characters LCD screen
- 15 LEDs to display important information
- Non-Volatile memory ensures no loss of data even if power supply is accidentally removed
- Wide range power supply
- Sounder strobe output provides 0.5 A / 24 V load, compatible with GST conventional sounders
- RS232 interface enables communication with PC, advanced user friendly programming software including ‘Fuzzy logic'
- RS485 (max 32 panels w/ card) or CAN (max 240 panels w/ card) interface enables networking, built-in RS485 repeater output (max. 10 repeaters)
- Optional panel printer and GMC graphic station
- PAS and Acknowledge Function, Dirty Detector Reporting, Walk Test Function

GST200N-2

GST200N Addressable 2 Loop Panel (English)

Technical specifications

Electrical

Power consumption	Standby: 21 Ah / 24 VDC
Operating voltage	100 to 240 VAC, 50/60 Hz
Current consumption	1.5 A

Loop

Maximum loop capacity	2
Quantity of devices per loop	235 (for 1st loop), 242 (for 2nd loop)
Cable rating	Min. 1.0 mm2, ideally 1.5 mm2, 1500 m

Zone

Maximum zone capacity	up to 30

Output

Output quantity	3
Output type and rating	Min. 1.5 mm2, ideally 2.5 mm2
Fire alarm signalling	500 mA / 24 VDC / NO-NC-Active
Fault signalling	NO / NC
Termination	4k7 ohm

Physical

Form factor	Large
Physical dimensions	580 x 420 x 202 mm (H x W x D)
Mounting type	Surface mount

Environmental

Operating temperature	0 to +40°C
Relative humidity	≤95% noncondensing
IP rating	IP30

Regulatory

Certification	CE, LPCB
Standards	EN54-2 EN54-4

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 12 June 2024 - 6:02