240320

Conventional DIN manual call point, Hausalarm

General

The 240320 is a BLUE, type-B, buble action manual call point for surface mount applications.

Construction

In comparison with plastic cases, the robust design housing made of die-cast aluminium proves to be of advantage even after years of use, thanks to its resistance to environmental impact. It is virtually unbreakable, form stable and hardly changes its colour in sunlight.

Numerous design details, such as the self-closing lock cover, protect the interior from dust or water penetration and facilitate mounting and cabling. The protection class is IP43.

Safety

The door with the easily replaceable glass pane has an opening angle of over 180°. When the call point is activated, the door is mechanically prevented from closing



Details

- Conventional technology
- Alarm LED for activation indication
- Operating instructions using standardised EN54-11 symbols
- Attractive design with a housing made of robust die-cast aluminium
- Designed for surface mount applications
- EN standard type B manual call point, dual action
- 1000 Ohm series resistor fitted

240320
Conventional DIN manual call point, Hausalarm

Technical specifications

General

Status indication	LED
Connectivity	2-wire zone

Electrical

Power supply type	Zone angetrieben
Operating voltage	10 to 30 VDC
Cable specification	<1.5 mm²
Terminals	6

Detection

Detection principle	Manual activation
Monitoring	Off, On
Installation height	Determined by local regulation

Output

Output quantity	1
Output type and rating	Contact (25 VAC @ 2 A or 60 VDC @ 2 A)

Physical

Physical dimensions	127 x 127 x 35 mm (W x H x D)
Net weight	420 g
Colour	Blau (RAL 5015)
Mounting type	Oberflächenmontage, Wandmontage
Material (body)	Aluminium-Druckguss
Functional marking	HAUSALARM

Environmental

Vandal proof	No
Operating temperature	-25 to +70°C (max. 12 h) -20 to +60°C (continuous operation)
Relative humidity	5 to 95% noncondensing
Environment	Drinnen
IP rating	IP43 (standard)

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE

Compatible products

Category	Reference	Description
Detection device	DM966	Replacement clear windows for push-button activated manual call points



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 29 April 2025 - 9:10