AS364M

Conventional fire sounder, multi tone with deep base (mains powered)

General

The AS364M is a general purpose electronic sounder for alarm applications.

Efficient and versatile

The AS364M provide high sound output at a low current, thus reducing power requirements and system cost. The AS364M sounder is supplied with a volume control as standard, allowing final audio adjustments to be made during installation.

With a choice of 32 different tones (see tones table in manual), which are switch selectable, the required tone can be selected during installation.

The mechanism for locking the sounder to the base, can be activated if required. Once activated, a special tool is required to remove the sounder from the base.



Details

- High sound output
- 32 Tones user selectable
- Automatic syncronisation
- Volume control
- Anti-Tamper locking mechanism
- Deep mouting base

AS364M

Conventional fire sounder, multi tone with deep base (mains powered)

Technical specifications

Electrical

Operating voltage	110/220VAC 50/60Hz
Current consumption	80 mA (depends on tone selected)

Sounder

Output level	Sound output at 1 m (depends on selected tone): 89 to 102dB(A)
Selectable tones	32
Synchronization	Phased start (automatic)

Physical

Physical dimensions	100 x 104 mm (Ø x D) (shallow base)
Net weight	250 g
Colour	Rød
Material	Polycarbonate haut impact

Environmental

Operating temperature	-25 to +55°C
Environment	Indendør, Udendørs
IP rating	IP65

Compatible products

Category	Reference	Description
Notification device	AS36RIM	Sounder Beacon Rim With "Fire" Text (English)

EDWARDS
Built for Resilience

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 22 July 2025 - 13:39